

Connect-itMODULAR CEILING MOUNTS

FOR MEDIUM TO EXTRA LARGE SIZED DISPLAYS

THE NEXT LINE UP OF THE CONNECT-IT SYSTEM

Vogel's Professional introduces the modular Connect-it ceiling mounts for 32 to 65 inch displays, in addition to the existing Connect-it ceiling mounts for 15 to 32 inch displays. With this extension, Vogel's Professional provides the solution for almost every situation.

Key features of Connect-it:

- Flexible modular system
- Modular display interface for a perfect fit
- Multiple display mounting with standard components
- Quick and easy installation

The Connect-it range for medium to extra large sized displays includes:

- **Ceiling plates** The ceiling plates are part of the modular system which enables you to create a ceiling mounting solution for displays. The 4 different ceiling plates provide solutions for flat ceilings, inclined ceilings and truss systems.
- Poles The aluminium poles are the basis of the Connect-it modular system for medium to extra large sized displays. Main features: Quick and easy installation, large cable management system of 4 separate channels, multiple display mounting, customizable insert. The aluminium poles are available in 3 different lengths (80, 150 and 300 cm) and can easily be cut to a desired length.

Modular display interface

The modular interface consists of two separate components: an interface bar and a set of 2 interface display strips. The interface bar is for the horizontal display fitment and the interface display strips are for the vertical fitment. This creates a custom fitment for any display. With these standard components it is also very easy to create multiple display solutions.

- Interface bars The horizontal fitment determines the length of the interface bar and is available in 4 different lengths from 515 to 1175 mm.
- Interface display strips The vertical fitment determines the length of the 2 interface display strips and is available in 6 different lengths from 380 to 1130 mm.







THE NEW WAY OF DISPLAY MOUNTING

Modular display interface

Consists of two separate components

- Interface bar
- Set of 2 interface display strips

Interface bar

- Available in 4 different lengths to exactly match any display
- Max. horizontal fitment: 1110 mm



Cable management

Multiple CIS® (4 channels), neatly hides all cables





Positioning

Applicable for landscape and portrait mounting






Interface display strips

- Available in 6 different lengths to exactly match any display
- Max. vertical fitment: 1100 mm







Multiple display solutions

Easy way of creating a mutiple solution









CEILING PLATES

PUC 1060

- Ceiling plate suitable for flat ceilings
- Max. load (2x) 80 kg / 176 lbs

PUC 1070



- Ceiling plate suitable for inclined and flat ceilings
- Fixed display position to the ceiling plate
- Max. load (2x) 80 kg / 176 lbs

PUC 1080



- Ceiling plate suitable for inclined and flat ceilings
- Multi directional
- Max. load (2x) 80 kg / 176 lbs

PUC 1090



- Truss adapter for 51 mm truss systems
- Max. load (2x) 80 kg / 176 lbs

POLES



- Poles PUC 25xx Series in 3 different lengths
- Multiple cable management, CIS®
- Easy to customize
- Aluminium, easy to cut to length
- Max. load (2x) 80 kg / 176 lbs

	length
PUC 2508	80 cm
PUC 2515	150 cm
PUC 2530	300 cm






- Interface bar PFB 34xx Series in 4 different lengths to exactly match any display
- Stylish aluminium design
- Max. load 80 kg / 176 lbs


	length	max. horizontal fitment
PFB 3405	515 mm	450 mm
PFB 3407	715 mm	650 mm
PFB 3409	915 mm	850 mm
PFB 3411	1175 mm	1110 mm

PFS 33XX Series



- Interface display strips PFS 33xx Series in 6 different lengths to exactly match any display
- Incremental tilt function 10-15-20°
- Autolock® locking system
- Stylish design
- Max. load 80 kg / 176 lbs
- Security (optional)

	length	max. horizontal fitment
PFB 3405	515 mm	450 mm
PFB 3407	715 mm	650 mm
PFB 3409	915 mm	850 mm
PFB 3411	1175 mm	1110 mm





Request our extensive catalogue with our entire range of solutions: www.vogels.com/profcat

PX 70250 © 01/2011 Vogel's Holding BV 2011 © all rights reserved.